

and the second second

Gro-Lux LED Linear GROLUX LED LINEAR UNIVERSAL X6 0020916

Product features

IP66 rated • PPF efficacy up to 3.06 mol/J • Life time 50,000Hrs L70B50 • To be used with a SELV driver



PRODUCT OVERVIEW

IPC Code	0020916
Product name	GROLUX LED LINEAR UNIVERSAL X6
Technology	LED
Cap/Base	Cable
Fixture rating	Enclosed
Certifications	00
ETIM Class	EC000996
Light colour	Grolux
Beam Angle (°)	120
Average life (Nominal) (h)	50000
IP rating	IP66
Product EAN number	5410288209166

DATA TABLE

General data	
IPC Code	0020916
Product name	GROLUX LED LINEAR UNIVERSAL X6
Technology	LED
Cap/Base	Cable
Fixture rating	Enclosed
Certifications	00
ETIM Class	EC000996
Optical data	
Light colour	Grolux
Beam Angle (°)	120
Beam angle (Rated) (°)	120
Electrical data	
Lamp power factor	1.0
No. Of switching cycles before premature failures	100000



Gro-Lux LED Linear GROLUX LED LINEAR UNIVERSAL X6 0020916

Drive current (mA)	1400
Lifetime data	
Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000
Physical data	
IP rating	IP66
Weight (kg)	5.52
Packaging	
Single packaging type	Without Packaging
Product EAN number	5410288209166
Packaging single length / height (cm)	100.0
Packaging single width (cm)	2.6
Packaging single depth (cm)	4.0
DUN14 (outer)	05410288209166
Units per outer package	1
Packaging outer length / height (cm)	114.0
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	12.0
Safety data	
Special purpose lamp	Yes
Suitable for household illumination	No

PHOTOMETRY

